



aluDOOR

THE NEW, PREMIUM ENCLOSURE GENERATION, INCLUDING DOOR

IP 66, IP 67, IP68 (1.2 m; 2 h), IP 69K

The key product features:

- Enclosure material: diecast aluminum
- Enclosure surface: powder coating, RAL 7016
- 100° opening angle
- Structurally integrated lid hinges
- · Integrated recess in lid for membrane keypad or front plate
- Stainless steel lid screws and threaded inserts
- Enclosure lid without or with recess for fitting a membrane keypad or product label
- Clip-on design covers
- Enclosure seal: PUR
- Honored with the German Innovation Award 2023

aluDOOR enclosures are a further development of the unique series aluCASE. This enclosure has an unmistakable progressive design. They are the modern, contemporary »packaging« for innovative industrial electronics.

The integration of true hinges without additional expenditure has been implemented successfully in the new series. After the »mounting« of the lid and the fixation with the securing screws, they turn into »compact cabinets« with stainless steel screws and stainless steel threaded bushings. Even under extreme operating conditions, this arrangement ensures an absolutely safe and permanent closure technology.

aluDOOR enclosures are available either with recesses in the lid for the installation of membrane keypads (ADF) or with a flat lid (ADO).

Finally, the installation level of the enclosures is covered by design covers made of aluminium (finished in matt silver), providing an unparalleled design. All enclosures have domes in bottom sections and lids for the secure fastening of installations.

Enclosure sizes

10 - with 2 lid variants: ADF = Series with recess in the lid and ADO = Series with flat lid

Further information

Integrated hinge function on side D with 2 securing screws (A2, self-forming) Captive lid secured with two screws Fastening with closed enclosure Clip-on design covers, coated silver matt Opening angle of the lid max. 100°

Enclosure

Die cast aluminium alloy EN AC-44300 DIN EN 1706 (GD Al Si 12/DIN 1725) 1° mould slope for casting ejection > Internal circumference dimensions decrease by 1° towards enclosure base





Fastening

Separate screw channels

Internal mountings

Fastening domes with M5 thread on the enclosure bottom and in the lid

Ingress protection IP 66, IP 67, IP 68 (1.2 m; 2 h) / EN 60529, IP 69K / ISO 20563

Gasket

Foamed, polyurethane (PUR) Optional: Silicone seal Optional: EMC gasket

Surface

Powder coating, RAL 7016 Design covers, silver matt powder coating Optional: Special colours Optional: Corrosion protection

Lid screws Stainless steel 1.4567, M5 with TX25, captive

Lid fastening thread Casting sleeves, stainless steel A2

Hinge Securing screws M5 self-forming for hinge attachment

ROLEC Service Utilise our full service offer for installation-ready enclosures



Our passion is enclosures.

https://rolec-usa.com

Photo	No.	Туре	Length L	Width W	Height H	Gasket H	Optional available
	133.090.000	ADF 090	120	90	70	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.092.000	ADF 092	160	90	70	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.110.000	ADF 110	140	110	80	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.112.000	ADF 112	200	110	80	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.130.000	ADF 130	160	130	80	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.132.000	ADF 132	220	130	80	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.150.000	ADF 150	180	150	90	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.152.000	ADF 152	260	150	90	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.170.000	ADF 170	200	170	90	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	133.172.000	ADF 172	280	170	90	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	134.090.000	ADO 090	120	90	70	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	134.092.000	ADO 092	160	90	70	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
•	134.110.000	ADO 110	140	110	80	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	134.112.000	ADO 112	200	110	80	Silicon-gasket	- Corrosion proof coating - EMC-Shielding - Supporting rail for series terminals

terminals - Mounting plates



https://rolec-usa.com

Photo	No.	Туре	Length L	Width W	Height H	Gasket H	Optional available
	134.130.000	ADO 130	160	130	80	Silicon-gasket	- Corrosion proof coating - EMC-Shielding - Supporting rail for series terminals - Mounting plates
	134.132.000	ADO 132	220	130	80	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	134.150.000	ADO 150	180	150	90	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	134.152.000	ADO 152	260	150	90	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	134.170.000	ADO 170	200	170	90	Silicon-gasket	 Corrosion proof coating EMC-Shielding Supporting rail for series terminals Mounting plates
	134.172.000	ADO 172	280	170	90	Silicon-gasket	- Corrosion proof coating - EMC-Shielding - Supporting rail for series

Supporting rail for series terminals
Mounting plates