

multiPANEL

THE PREMIUM DESIGN HMI ENCLOSURE

(UL approval only valid for MPD 7000+7011)

IP 65

The most important product features:

- Enclosure material: aluminum profiles, stainless steel decorative inlays
- Enclosure surface: body and rear wall or doors RAL 9005
- Profile enclosure high-precision production from 150 x 150 mm to 800 x 800 mm
- Firmly glued aluminum front plate
- 2 enclosure heights: 70 and 85 mm
- Connection to the profiPLUS 50 and taraSMART suspension systems
- Enclosure seal: Silicone foam

To configure this product, please contact us without obligation. We are happy to help.

multiPANEL offers the option of integrating every conceivable application. The enclosure front facilitates the permanent installation of a front plate or glass front, e.g. for touch applications. Almost borderless, with flush installation and permanently connected with the enclosure. Suitable cut-outs for switches and more are included in the service provided by ROLEC, and are established in the production department at the German headquarters in accordance with customer specifications.

With the flat multiPANEL 70 version, the rear wall is optionally available with a flush rear wall, which can be supplied as a fully bolted version, bolted with hinges or with locks and hinges. multiPANEL 85 is also available for an even greater enclosure depth. Internal mountings can naturally also be installed in the door. For this purpose, stays are fitted inside the door on request by the customer, in preparation for the technical installation.

Enclosure sizes

Made to customer required sizes L x W x H max. 800 x 800 x 70/85 mm

Additional infos

Puristic, multi-variable design for modern machines Profile enclosure – produced to the precise millimetre

Two enclosure depths: 70 and 85 mm

Material/Colour

Extruded aluminium

Aluminium corner pieces mounted with aluminium profiles

Standard front plates: Aluminium 3 mm, Al Mg 1, silver anodised Optional: Finished front plates, lasered, engraved or printed

Membrane keypads ready for installation

Optional handle: POM RAL 9005, with stainless steel inlay V2A



Fastening

With the suspension arm systems profiPLUS 50 or taraSMART Panel coupling

Internal mounting

Slide-in contour for spring nuts M4/M5

Ingress protection

IP 65 / EN 60529

Gasket

Silicone foam

Surface

Powder coating RAL 9005 Deep black, fine structure

Optional: other colours

Customising

Learn more about our full customising service for installation-ready enclosures



https://rolec-usa.com

Our passion is enclosures.

Photo	No.	Туре	Length L	Width W	Height H	Gasket H	Optional available
	320.000.001	MPD 7000 - bolt	ed rear 0 wa	II O	0		HandleWall pivot mountProfile handle
	320.110.001	MPD 7011 - bolt	ed dooi0	0	0	Silicon-gasket	- Handle - Wall pivot mount - Profile handle
	320.112.001	MPD 7012 - doo	rwith loocks	sand hin0go	es 0	Silicon-gasket	 Wall pivot mount Profile handle Handle Protection Class IP 65
	320.850.001	MPD 8500 - bolt	ed rear0wa	II O	0	Silicon-gasket	 Wall pivot mount Profile handle Handle Protection Class IP 65
	320.851.001	MPD 8511 - bolt	ed dooi0	0	0	Silicon-gasket	 Wall pivot mount Profile handle Protection Class IP 65 Handle Hinges
	320.852.001	MPD 8512 - doo	rwith loocks	sand hin0go	es 0	Silicon-gasket	 Wall pivot mount Profile handle Handle Protection Class IP 65
	501.100.200.	Wall Pivot Moun	t profiP A NI	EL 0	0		-
	503.320.150	MPD 00 - bolted	rear w a ll	0	0		- Corrosion proof coating
	503.320.380	Keyboard tray 38	80mm, fi gio	d 0	0		- Corrosion proof coating
	503.320.381	MPD 00 - bolted	rear w all	0	0		- Corrosion proof coating
	503.320.450	Keyboard tray 4	50mm, fi gio	d 0	0		- Corrosion proof coating
	503.320.451	MPD 00 - bolted	rear w a ll	0	0		- Corrosion proof coating
	522.320.001	Handhold	0	0	0		-
	522.320.BBB	Handhold	0	0	0		-