
# Enclosure series polyTOP

Type: PT 100

Material-No.: 132.100.000





\* Please note: Mould slope for casting ejection, dimensions in the amount of the bottom!

Enclosure material	Polyester GrP, UL 94 V-0, RAL 7032, pebble grey	Ingress protection	IP66 EN 60529
Lid screws	4x Polyamied (PA), captive	 Weight	520 g
Gasket	1x EPDM, black	Tolerance	DIN ISO 16901 T-130 (outside dimensions ±0,5mm)





## 132.100.000 polyTOP PT 100



#### Product overview

Material	Polyester
Protection Class	IP 66/EN 60529, IP 67/EN 60529
Color	RAL 7032
Certifications	CSA (optional), Germanischer Lloyd (optional), UL (optional)
Length (L)	4.02 inch
Width (W)	4.02 inch
Height (H)	3.19 inch
Weight (g)	520 g





### polyTOP

THE ROBUST POLYESTER ENCLOSURE

#### IP 66 - Optional: IP 67

#### The key product features:

- · Enclosure material: glass-fibre reinforced polyester
- Enclosure surface: similar to RAL 7032
- · Lid screws in polyamide
- · Compatible assembly dimensions with the aluNORM series
- Flammability: UL-94 V0
- Enclosure seal: O-ring gasket (EPDM)

---

polyTOP is a range of IP 66 enclosures made of highly resistant glass-fibre reinforced polyester. The enclosures are ideal for industrial electronics and control equipment used in harsh indoor and outdoor applications.

Special features include corrosion-resistant polyamide lid fixings in four different designs: slotted (standard), triangular or square head for tamper protection, and hand screws for fast access. Threaded M6 fixing pillars are provided inside for mounting terminal rails, circuit boards, mounting plates etc. polyTOP is available in a wide range of standard sizes. Supporting rails, terminals, cable glands and other accessories are also available.

We can supply polyTOP enclosures fully customized to your requirements.

#### Enclosure sizes

13

#### **Further information**

Improved technology thanks to the single-channel lid and assembly fastening Compatible assembly dimensions with the aluNORM range Full protective insulation in accordance with VDE 0100

#### Enclosure

Polyester glass fiber reinforced, halogen-free similar to RAL 7032, pebble gray, surface resistance< 109 Ohm Optional: similar to RAL 9005, deep black, surface resistance< 109 Ohm 1° mold slope for casting ejection > internal circumference dimensions decrease by 1° towards enclosure bottom.

#### Flammability

UL 94 V-0

#### Fastening

Single-channel lid and assembly fastening outside of the enclosure interior, stainless steel external mounting brackets





Internal mounting M4/M6 threaded bushing on the enclosure base

Ingress protection IP 66 / EN 60529 Optional: IP 67 / EN 60529

Gasket EPDM O-ring gasket Optional: Silicone gasket

Lid screws Polyamide, corrosion-resistant and captive, slotted design Optional: Various locking screws available

Customizing Learn more about our full customizing service for installation-ready enclosures

# **Full-Service-Products**

Customization according to your wishes.





Everything begins with individual advice. We'll be pleased to support you with your project and find solutions for every requirement. Customer-specific solutions are our speciality.



Test our products with your internal mounting. We'll be pleased to send you a sample enclosure for inspection with no strings attached.



We'll manufacture every enclosure for you according to your exact specifications - whether they involve precise drilling or large tolerance.



Thanks to our modern CNC production, we can quickly and efficiently mill custom-fit cut-outs and contours to match your exact specifications.



Our services also include engraving your logo and other elements, which we can of course perform in any colour you desire.



We can process stainless steel enclosures and plates quickly and reliably according to your individual requirements thanks to our in-house lasering centre.



We can powder coat enclosures, command enclosures and suspension systems in any RAL colour you desire. Custom colours are of course also possible.



We can also paint all our enclosures in any RAL colour you desire. The application of primer and special colour

structures are possible, as well.



If desired, we can apply your logo and lettering or other markings using serigraph printing.



Digital printing is particularly worthwhile for low-volume order s and for realising complex pa tterns or images.



We offer our conFORM low-price standard EMC enclosure to protect your internal mounting against electromagnetic radiation. On request, we can also supply an EMC-compliant version of any other ROLEC enclosure.

If you have any requirements for services not listed here, please ask us. Customer-specific solutions are our speciality. We also are keen to take on unusual tasks.

We will help you with those challenges that many others would give up on.

**Our Service** 



We are able to offer the right made-tomeasure display for all our enclosures - in varying sizes and degrees of robustness depending on the application.



ROLEC's portfolio also includes matching front plates, mounting plate, supporting rails and terminal blocks as well as a range of cable glands, blanking plugs etc.



Would you like to have all your components supplied already assembled? No problem. Our assembly team will be pleased to perform all assembly work on your behalf.